

Name	PT 232	PT 233	PT 234	iS29	iS4219
Display					
Active screen dimensions, diameter, (h x v) mm	4x1 LCD,	3x1 LCD,	930x243	29" 697.7 x 261.5	42", 930.2 x 523.2 + 19", 376x301
Resolution	64 x 96 / matrix	64 x 96 / matrix	1920 x 502	1366x480	1920x1080
Viewing angle (typical)	178°	178°	178°	176°	176°
Brightness (typical)	2000 cd/m ²	2000 cd/m ²	1000 cd/m ²	1000 cd/m ²	1000 cd/m ²
Colour performance	blue/white	blue/white	16.7M colors	16.7M colors	16.7M colors
Panel technology	LCD	LCD	TFT	TFT	2x TFT
Backlight system	LED	LED	LED	LED	LED
International Protection Rating					
IP code	IP65	IP65	IP65	IP65	IP54
Vandal-proof	DIN 18032/3	DIN 18032/3	DIN 18032/3	DIN 18032/3	DIN 18032/3
Power					
Power supply	230V AC	230V AC	230V AC	230V AC	230V AC
Average consumption			200 W		250 W
Maximum consumption	371 W	295 W	553 W	90 W	314 W
Environmental conditions					
Temperature	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)
Dimensions & Weight					
H x W x D (mm)	1840 x 452.5 x 268	1500 x 452.5 x 268	1500 x 503 x 266	900 x 650 x 606	1610 x 710 x 240
Weight	130 kg	108 kg	115 kg	110 kg	170 kg
Colour					
Standard Colour cabinet	RAL5002	RAL5002	RAL5002	RAL5002	RAL5002
Customized colour	On request	On request	On request	On request	On request
Manageability					
SNMP v3, damage, door opening, voltage levels, interior exterior temperatures, cooling and heating systems					
Options					
Wall mount bracket, ceiling mount bracket, tilt wall mount					