

Name	iS32	iS38	iS42	iS2x47	iS55	iS72
System						
Type	Stationary info display	Stationary info display	Stationary info display	Stationary info display	Stationary info display	Stationary info display
Side	single	single	single	single	single	single
outdoor/indoor	outdoor	outdoor	outdoor	outdoor	outdoor	outdoor
Display						
Active screen dimensions, diameter, (h x v) mm	32", 697 x 392	38", 930.2 x 243	42", 930 x 523	2x47", 1170x 1040	55", 1215x686	72", 1677x979
Resolution	1366 x 768	1920 x 502	1920x1080	1920x1080	1920x1080	1920x1080
Viewing angle (typical)	176°	176°	176°	178°	178°	178°
Brightness (typical)	1000 cd/m2	1000 cd/m2	1000 cd/m2	800 cd/m2	800 cd/m2	2000 cd/m2
Colour performance	16.7M colors	16.7M colors	16.7M colors	16.7M colors	16.7M colors	16.7M colors
Panel technology	TFT	TFT	TFT	TFT	TFT	TFT
Backlight system	LED	LED	LED	LED	LED	LED
International Protection Rating						
IP code	IP54	IP54	IP54	IP54	IP54	IP54
Vandal-proof	DIN 18032/3	DIN 18032/3	DIN 18032/3	DIN 18032/3	DIN 18032/3	DIN 18032/3
Power						
Power supply	230V AC	230V AC	230V AC	230V AC	230V AC	230V AC
Average consumption	100 W	100 W	100 W		200 W	500 W
Maximum consumption	117 W	157 W	175 W	431 W	275 W	1365 W
+Heating	300 W	100 W	300 W	300 W	300 W	450 W
+ air condition						
Environmental conditions						
Temperature	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)	(-20°C) - (+50°C)
Dimensions & Weight						
H x W x D (mm)	870 x 565 x 170.7	1500 x 400 x 192	1090 x 680 x 190.5	1392 x 1256 x 200.6	1410 x 880 x 240	1860 x 1160 x 236
Weight	54 kg	80 kg	90 kg	190 kg	100 kg	220 kg
Colour						
Standard Colour cabinet	RAL5002	RAL5002	RAL5002	RAL5002	RAL5002	RAL5002
Customized colour	On request	On request	On request	On request	On request	On request
Manageability						
SNMP v3, damage, door opening, voltage levels, interior exterior temperatures, cooling and heating systems						
Options						
Wall mount bracket, ceiling mount bracket, tilt wall mount						